Assembly Design Semantic Recognition Using SolidWorks-API

Baha A. Hasan and Jan Wikander Department of Machine Design, KTH Royal Institute of Technology, Sweden Email: bahasan@kth.se

Mauro Onori Department of Production Engineering, KTH Royal Institute of Technology, Sweden

Abstract-This paper describes a novel approach to recognize and model assembly semantic knowledge enclosed in product assembly features. The proposed approach is based on two stages: assembly semantic recognition and assembly semantic modelling. In the first stage, the internal boundary representation (B-rep) recognition method is utilized to extract assembly semantic knowledge from assembly CAD models using SolidWorks' API functions. In the second stage, a multi-level semantic assembly model is generated. The proposed assembly semantic model is characterized by separating geometrical semantic data represented by form features (basic geometrical and topological entities such as holes, slots, notches etc.) from assembly features (features significant for assembly processes such as mating, alignment, handling, joining etc.). Another characteristic for of the proposed approach is the ability to generate application-specific features based on the extracted geometrical, dimensional and positional semantic data from the assembly design. The generated application specific features will be used to integrate assembly design knowledge to the required assembly processes and resources in the assembly process planning (APP) in product life-cycle. A case-study example is included for illustration of the proposed approach. The work is part of the research within the Evolvable Production Systems paradigm and aims at linking product features to production equipment modules.

Index Terms—assembly, feature, form, mating, recognition, SolidWorks

I. INTRODUCTION

Modern manufacturing system paradigms have to cope with several critical issues in order to achieve the desired adaptability. The Evolvable Production Systems (EPS) paradigm, detailed in [1], [2], is one of the very few that attempts to dynamically link the product characteristics to its modular production equipment. One of the most critical challenges is the soft or logical support functions [3], such as assembly design and Assembly Process planning (APP) integration. If the APP to a larger extent can be performed automatically (and hence quickly) based on the available resources, the assembly system will be more dynamic and adaptive. This can be achieved by facilitating knowledge transfer between assembly design information and assembly process planning. One of the challenges for integrating assembly design and APP is that much of the product knowledge related to assembly design is lost during transferring from one design stage to another. To overcome this problem, features in product design have been proposed as a means to provide high- level semantic information for interfacing CAD to different applications throughout the product-life cycle [4].

In general, features of a product are classified into lowlevel features (form features), which are basic geometrical and topological entities such as holes, slots, notches etc. and high- level features, which are characterized by *both* a form and a specific application (machining, assembly, tolerance etc.). For example "*machining features*" can be defined as geometrical and topological entities significant for manufacturing function. The conversion of form features (low-level) into application-specific (high-level) features in terms of functionality, manufacturing and assembly is the overall aim of feature-based modelling [5]. In this context, an *assembly* feature could be realized as an association between two form features from different parts [6].

The term *Feature Recognition* (FR) refers to the different techniques that are used to extract the knowledge enclosed in geometrical and assembly representations of solid models in order for that knowledge to be used in manufacturing, process planning and other different downstream applications of the product life-cycle. During the last decades a lot of work has been published towards effective and smart automatic feature recognitions [7] and different methods have been reported in the literature [8].

From a geometrical point of view, feature representation is classified into two types: surface- based or volume-based. Surface features are based on topological entities such as face, edges and vertices with functional meanings on the part boundary; this representation is known as boundary representation (Brep). B-rep modelling decomposes a solid into its boundary surfaces or shells. Each shell can be decomposed into individual faces. Each face is described as a surface bounded by a loop of edges. Each edge is bounded by two vertices. Volumetric features are based on three-dimensional geometrical primitives such as

Manuscript received July 1, 2016; revised November 16, 2016.

sphere and cylinder. This representation is known as Constructive Solid Geometry (CSG). Based on this classification, feature recognition approaches can be classified as well into B-rep based approaches and CSG approaches. Since the B-rep CAD representation of features is widely and mostly used, the B-rep feature recognition approaches are the most common in published literature [9].

From an engineering point of view FR systems are divided into two methods; external and internal methods [10]. In internal methods the API (Application Programmable Interface) of the CAD software is used in order to extract topological, geometrical and assembly information relating to a part or an assembly. While in external methods, a CAD model file is exported in a neutral data format (e.g. STEP, IGES, ACIS). The exported file is then translated using compilers (interface programs) to be compatible for a specific application (e.g. commercial CAM system). Both methods have been used by researchers for FR.

In this paper, an internal B-rep CAD recognition approach is proposed for extracting semantics of assembly design. This approach is based on two stages: the first stage is assembly feature semantics recognition from SolidWorks (SW) CAD software using its API. The second stage is modelling of assembly design semantics. An assembly design semantic model is generated based on input from the B-rep recognition stage. The assembly design semantic model includes several sub-models: a form feature model for representing geometrical and tolerance design knowledge, a structural model for representing assembly part relations in product, and mating relation models for representing assembly design knowledge on component level, feature level and surface level. Fig. 1 illustrates the proposed approach, in which different aspects of assembly design knowledge (geometry, tolerance, kinematic and assembly relations) are recognized from SW by using SW-API.





 $Figure \ 1. \ \ Recognition \ and \ modelling \ of \ assembly \ feature \ semantics.$

This paper is divided as follows: Section II reviews the related research work in assembly design based on features. Section III introduces the assembly design semantic modelling approach. Section IV presents a case-study example. Section V describes the SW-API

recognition algorithm development. Section VI draws conclusions and provides some ideas for future work.

II. RELATED WORK

In the published literature, two research areas have been identified, in which assembly features have been used to improve efficiency, namely assembly modelling and assembly planning. Different definitions for assembly features have been proposed according to these two research areas.

From an assembly modelling perspective, assembly features are defined as "*Mating pairs of form features with parameters and compatibility constraints as part of each feature definition*" [11]. In this definition, a more specific assembly feature type called mating feature is presented, where mating feature (or conditions) is defined in [12] as "*relationships that involve contact between parts, as well as relationships in which two parts do not have contact (e.g. clearance conditions!*)". Mating features are classified further into plane mate feature (plane to plane mating relation) [13] and alignment feature (cylindrical to cylindrical surfaces) [14].

From an assembly planning perspective, assembly features have been defined as: "features with significance for assembly processes" [15]. The same author introduced more specific assembly features, from a process perspective: Connection features "such as final position, insertion path/point, tolerances" and handling features "characteristics that give the locations on an assembly component that can be safely handled by a gripper during assembly!". Also more specilized assembly features have been introduced such as joining features. A joining feature has been proposed [16] to represent assembly/joining relations, and it includes joining entities, joining methods, constraints and groove shapes.

Many researchers try to develop assembly design representation based on assembly features by introducing new concepts or by expanding the assembly feature concept. Shyamsundar et al. [17] introduces a representation of the assembly (called the AREP), which stores assembly hierarchy as well as relations between components and sub-assemblies. In AREP, relations are defined in terms of assembly features, which are classified into relational assembly features, thus indicating the relation between geometric features, and assembly form features indicating the joining of two form features from different parts. Singh et al. [18] propose assembly ports to group and automate mating relations between parts. An assembly port is distinct from assembly feature in the sense that an assembly port is the low-level geometrical entity (e.g. peg), which will be connected to another assembly port (e.g. hole) though an assembly feature (peg-hole connection). Their work is an attempt to separate geometrical information (assembly port) from assembly information without a clear structure for the low level geometrical entities that form the assembly port. A "design unit" concept, or sub-assembly model, is presented by Myung and Han [19] in order to capture more knowledge about the relation between form features in part assembly and functional design features. A semantic modelling approach is proposed by [20] in the SPIFF system. SPIFF is a web-based, collaborative modelling system based on multiple-view feature modelling [21]. In this approach, a feature is described over a well-defined meaning, or semantics, specified in classes. The classes specify the properties of the features as structured instances. According to [22], in the semantic approach the whole modelling process is "uniformly carried out in terms of features and their entities" (e.g. faces and parameters), and of constraints among these entities. Users can define their own feature classes based on existing feature classes. Feature classes are then stored in feature libraries, from which new features can be instantiated during a modelling session. The most important characteristic of the semantic feature modelling, beside its adaptability in defining new feature classes, is that the semantics of all features is "effectively maintained throughout model evolution". These characteristics of the semantic feature modelling lead to a two-level structure in the semantic feature model, clearly distinguishing "modelling entities (entities on which all modelling operations are performed)" from entities in "the evaluated geometric representation of the product model". More details about feature semantic approach are presented in [22].

An assembly semantic modelling approach is proposed in [23] and [24]. In this approach assembly semantics is defined as "the abstract description of assembly relationships, which implies the constraint between parts, assembly rule, assembly knowledge and assembly action" [24]. The proposed assembly semantic model includes the joint relation, position relation and transmission relation of the assembly. According to [23], the benefits of assembly semantic modelling are simplified interaction and capturing of design intention, expressing rich assembly constraints (position constraint; dimensional constraint, kinematics constraint) and implying assembly precedence relationship knowledge.

A more detailed assembly semantic modelling approach is presented by Hui *et al.* [25], where assembly information is described by a three-level semantic abstraction: conceptual level, structural level and part level. Ma and Tong [26] expand the assembly feature concept by proposing a semantic feature concept including so called associative features (AFs), An associative feature is "*a set of semantic relationships among product geometric entities, which can be defined as a single object entity in an engineering application*" [26].

As a conclusion from this section, three points have to be taken into consideration in modelling assembly features for process planning:

- Assembly feature semantics should include geometrical, non-geometrical, functional and assembly relations.
- The assembly feature concept must be further specified by mating features. Mating features have to further "expand" to include more details about

geometrical entities by defining joining features. Mating and joining features are essential for specifying assembly process planning, since joining processes will take place on mating entities.

• It is preferable to separate geometrical knowledge from assembly knowledge to enable more options for designers, in the detailed design phase, for changing geometry while keeping the assembly information.

III. ASSEMBLY DESIGN SEMANTIC MODEL

Based on the literature study in the previous two sections, the assembly design semantic model generated from the B-rep recognition stage should include full description about assembly design in order to determine the required assembly processes and resources in APP. The proposed assembly design semantic model is illustrated in Fig. 2. The model is composed of five levels: assembly level, part level, feature level, B-rep entity level and application specific level.

In Fig. 2, the first and the second levels are for assembly part structure knowledge in the product design. Each product is composed of several subassemblies, and each subassembly is composed of at least two parts. The third level is a feature layer, where two associated form features from different parts are connected via an assembly feature.

The feature level represents the feature-based assembly modelling for the product. The next layer represents the B-rep model extracted from the geometric/part modeller. On the next level the assembly knowledge and the form feature semantic knowledge are both deployed to generate more specialized application-specific features. Surfaces of the B-rep model are classified into mating surfaces, represented by mating (for planar surfaces) and alignment (for cylindrical surfaces) features, and nonmating surfaces, some of them are represented by handling features. Handling features will be further specialized into gripping, feeding and fixturing features for each part in the assembly.

In order to determine joining features, mating surfaces are further analyzed by determining attributes of the contact area between mating entities. This is done in order to capture information related to potential joining processes. An example for contact area attributes are groove face, root edge, root opening and root angle (Fig. 3). The identification of those attributes facilitates the determination of the required joining process. For the attributes illustrated in Fig. 3, the joining process will be welding and the contact area attributes will be known as welding features.

Another important information that could be identified from mating surfaces is the hole pattern. A hole pattern has several attributes that could help to determine a specific joining process. One of these attributes is the hole type. Identification of a hole as threaded determines screwing as a joining process to follow.

Positional and dimensional information of form features are important for determining the required joining processes. Positional information helps to determine the relative positions of the form features, where for example overlapping between the mating entities, with unthreaded holes, indicates riveting as a joining process.



Figure 2. Assembly design semantic model.



Figure 3. Contact area parameters for welding process.

Dimensional parameters of form features will aid in determining fit relations between mating surfaces. Three types of fit relations are mentioned in literature, clearance fit between hole and shaft, which is identified if the minimum allowable dimension of a hole is larger than the maximum allowable dimension of a shaft. Transition fit, which is identified if the minimum allowable dimension of a hole is smaller than the maximum allowable dimension of a shaft, and the maximum allowable dimension of a shaft. The last type of fit is interference fit, which is identified if the maximum allowable dimension of a shaft. The last type of fit is interference fit, which is identified if the maximum allowable dimension of a shaft. The last type of fit is interference fit, which is identified if the maximum allowable dimension of a shaft. Identifying fit relations will aid in determining the type of fit process whether it is press fitting (for interference fit) or shrink fitting (for other fit types).

The assembly semantic model will be further illustrated by a case-study example in the next section.

IV. CASE-STUDY

The case-study example (press tool assembly) is shown in Fig. 4 (a). Fig. 4 (b) shows the press tool assembly composed of two major subassemblies: moveable half and fixed half subassemblies. The moveable subassembly is composed of top plate and guide bush subassembly (4 pieces). While the fixed subassembly is composed of guide pillar subassembly (4 pieces) and bottom plate. The press tool assembly model is decomposed into its form feature level (boss, hole, chamfer), and further into its Brep model (cylindrical surfaces (Cyl) and planner surfaces (Pla)). Structural (assembly part relation), geometrical and assembly knowledge enclosed in Fig. 4b will be further analyzed through structural, form feature and assembly relation models. Assembly relation models will capture assembly relations on part level, feature level and surface level.

The structural model (assembly part knowledge) is illustrated in Fig. 5, where all different parts and subassemblies are connected with each other through a guide pin pattern (four-hole pattern).





Figure 5. Structural model for the press tool assembly.

The form feature model is shown in Fig. 6. Each of the different parts in the press tool assembly is decomposed into its form features. Each of the form features is characterized by positional and dimensional semantic knowledge. Dimensional knowledge includes dimensions (width, height, diameter etc.) and dimensional and geometrical tolerances (line profile, surface profile, surface finish etc.). Positional knowledge is needed in order to determine the location of the form feature in the three dimensional space. The orientation of the form feature is represented by three independent angles: θ (rotation about x axis), Ψ (rotation about y axis) Φ (rotation about z axis). The 6-D configuration of form

features is used as a reference in an assembly as well as establishing and providing configuration relationships (ex. overlapping) between two features.

The assembly (mating) relations on part level, feature level and surface level are illustrated in Fig. 7, Fig. 8 and Fig. 9 respectively. In Fig. 7 the two types of mating relations are shown between different parts in the press tool assembly: coincident (Cod) and concentric (Con). More specific illustration for the two mating relations on the form feature level is given in Fig. 8 and on the surfaces included in those features in Fig. 9.



Figure 6. Form feature model for press tool assembly.



Figure 7. Mating relations on part level in press tool assembly.



Figure 8. Mating relations on feature level in press tool assembly.



Figure 9. Mating relations on surface level for press tool assembly.

Next section will discuss the generation of those models by using SW-API.

V. SW-API RECOGINTION ALGORITHMS

SW-API is an interface that allows exchange of data between CAD design and different software applications. SW-API consists of function calls which are used to access the data structures and their contents from SolidWorks software. The SW-API supports several programming languages such as VBA (Visual Basic for Application), VB.NET, Visual C#, Visual C++ 6.0, and Visual C++/CLI [27]. The API is used by writing function calls, which provide linkage to the required subroutine for execution. Microsoft VBA is embedded inside SolidWorks software, which enables the recognition process by calling SW functions from the code written in VBA.

Everything in SW is considered an object to the SW-API, those objects are not actually the thing itself, but "interfaces" to those objects. There are three main SW document types: Parts, Drawings and Assemblies. Each document type has its own object (*PartDoc*, *DrawingDoc* and *AssemblyDoc*) with its own set of related objects and functions. Fig. 10 illustrates a part of the SW-API object model.



Figure 10. Object model for SW-API.

In Fig. 10, The *ModelDoc2* object provides direct access to the *PartDoc*, *AssemblyDoc*, *DrawingDoc*, *PartDoc*, *DimXpert* and *DimXpertManager*. Each of

these documents has its own specific objects and their related functions. For example the AssemblyDoc::Mate2 object exists in AssemblyDoc document because adding and extracting mate relation is specific to AssemblyDoc. Beside the specific objects, which are belonging to a specific document, general objects are available on ModelDoc2 such Feature. FeatureManager. as *Configuration*. *SelectManager* and *Sketch*. Those general objects could be accessed by different documents in the SW-API. The proposed B-rep FR algorithm is based on geometry and topology of the parts and the mate relation between parts in an assembly. We can access the geometry / topology and mate information through API objects in the Feature Manager Design Tree. The Feature Manager Design Tree is the area in the SolidWorks GUI that shows the parametric CAD data of the active document. Fig. 11 shows SW Feature Manager Design Tree for the press-tool assembly. The data displayed includes information regarding parts name, construction history, annotations and assembly mates.

🕫 🖹 🐣	;
8-	
🖗 🎕 Press-tool Assembly (Default <display state-1="">)</display>	1
🕂 🛅 History	
- @ Sensors	
🕀 🖾 Annotations	
- Tront Plane	
- Top Plane	
- 🔆 Right Plane	
🕂 🕹 Origin	
🗄 🧐 🎕 (f) Bottom Plate<1> (Default< <default>_Dis</default>	play State 1
🗄 🧐 🎕 (-) Guidpillar<1> (Default< <default>_Display</default>	y State 1>)
🗄 🧐 🎕 (-) Guidpillar<2> (Default< <default>_Display</default>	y State 1>)
😑 🧐 🎕 (-) Guidpillar<3> (Default< <default>_Display</default>	y State 1>)
🗄 🕙 Mates in Press-tool Assembly	
🔅 🛅 History	
- 🙆 Sensors	
🕀 🔝 Annotations	
In the second secon	
🔆 Front Plane	
🖄 Top Plane	
- 🔆 Right Plane	
- I+ Origin	
🖶 💽 Boss-Extrude1	
Chamfer1	
Chamfer2	
🗄 🧐 🎕 (-) Guidpillar<4> (Default< <default>_Display</default>	y State 1>)
🗄 🧐 🎕 (-) GuideBush <1> (Default < <default>_Displa</default>	ay State 1>)
🗄 🧐 🎕 (-) GuideBush<2> (Default< <default>_Displa</default>	ay State 1>)
🗄 🧐 🎕 (-) GuideBush<3> (Default< <default>_Displa</default>	ay State 1>)
🗄 🧐 🎕 (-) GuideBush<4> (Default< <default>_Displa</default>	ay State 1>)
🗄 🧐 🎕 Top Plate<4> (Default< <default>_Display St</default>	ate 1>)

Figure 11. Feature manger design tree for press-tool assembly.

A high abstract flowchart of the FR algorithm is shown in Fig. 12. The proposed algorithm is based on extracting three types of semantic knowledge from an assembly:

- Recognizing the related geometry knowledge enclosed in the geometry representation of the part/assembly model as a B-rep model
- Recognizing of assembly knowledge relations enclosed in mating features from the assembly modeler.
- Recognizing non-geometrical dimensional and positional semantic knowledge related to form features in each part in the assembly from the geometric / part modeler.

The first step of the proposed algorithm is to read the assembly file from SolidWorks and loading it with extension *.SLDASM. The second step in the algorithm is to access each of the parts in the assembly for extraction of the features and sub-features using the *IFeature* interface functions, which allows access to the

feature type, name, parameter data, and the next feature in the Feature Manager Design Tree. Next step will be to extract the transformation matrix for each feature in the part. The SolidWorks transformation matrix is stored as a homogeneous matrix of 16 elements. The first 9 elements (a to i) are elements of a 3x3 rotational sub-matrix, the next 3 elements (j,k,l) define a translation vector, and the next single element (m) is a scaling factor. Extraction of the transformation matrix is achieved using the *MathTransform:: IGetData2* method.

The dimensional and geometrical tolerance information could be accessed by utilizing IDimXpert interface and its related objects, methods and functions such as: *DimXpertTolerance*, *DimXpertBlockTolerances*, *DimXpertDimensionTolerance*,

DimXpertSurfaceProfileTolerance, etc., each of these objects has access to a specific type of dimension or geometrical tolerance.



Figure 12. FR proposed algorithm.

Dimensions and tolerances have to be assigned to the SW part document by using DimXpert manger in order to be extracted by this method.

The next step is to extract topological and geometrical entities in each feature, which is done by utilizing the topology and geometry objects in SW-API such as *IBody2*. *IBody2* is the highest object that has to be accessed in order to get the related faces of the solid body,

which is defined as a three-dimensional volume bounded by faces. Using the *IBody2:: GetFaces* method will give access to the faces of the solid body. The surfaces is accessed by the same way by using *Iface::GetSurfaces* method.

The mating surfaces are extracted by using the Assembly Mate Extraction (AME) Algorithm proposed in [28]. In this algorithm mating entities (surfaces, edges etc.) are extracted using *Icomponent2::IMate2* and *ImateEntity2::GetMateEntities*.

VI. CONCLUSION

In this paper, an approach to recognize and model assembly design semantics in introduced. An internal Brep recognition approach is used. The advantage of this approach is the direct extraction of design data without using neutral data format, which might suffer from data loss during conversion from one format type to another. The disadvantage of this approach is the complexity of the recognition algorithms and the syntactical transfer of data. The future work includes more work on SolidWorks API to extract more design knowledge (ex. kinematic assembly knowledge) from an assembly, as well as a future integration of the model data to the EPS product knowledge bases.

REFERENCES

- M. Onori, N. Lohse, J. Barata, and C. Hanisch, "The IDEAS project: plug & produce at shop- floor level," *Assembly Automation*, vol. 32, no. 2, pp. 124-134, 2012.
- [2] H. Akillioglu, P. Neves, and M. Onori. Evolvable assembly systems: Implications and future research. [Online]. Available: https://www.diva-

portal.org/smash/get/diva2:382512/FULLTEXT01.pdf

- [3] H. ElMaraghy, *Changeable and Reconfigurable Manufacturing Systems*, Springer, London, 2009, p. 405.
- [4] M. Mantlya and S. Nau DS, "Challenges in feature-based manufacturing research," *Communications of the ACM*, vol. 39, pp. 77-85, 1996.
- [5] P. Stefano, F. Bianconi, and L. Angelo, "An approach for feature semantics recognition in geometric models," *Computer-Aided Design*, vol. 36, pp. 993-1009, 2004.
- [6] J. Shah and M. Rogers, "Assembly modeling as an extension of feature-based design," *Research in Engineering Design*, vol. 5, pp. 218-237, 1993.
- [7] B. Babic, N. Nesic, and Z. Miljkovic, "A review of automated feature recognition with rule-based pattern recognition," *Computers in Industry*, vol. 59, no. 4, pp. 321-337, 2008.
- [8] J. Shah, D. Anderson, Y. Kim, and S. Joshi, "A discourse on geometric feature recognition from CAD models," *Journal of Computing and Information Science in Engineering*, vol. 1, no. 1, pp. 41-51, 2001.
- [9] V. Sunil, R. Agarwal, and S. Pande, "An approach to recognize interacting features from B-Rep CAD models of prismatic machined parts using a hybrid (graph and rule based) technique," *Computers in Industry*, vol. 61, no. 7, pp. 686-701, 2010.
- [10] H. K. Miao, N. Sridharan, and J. J. Shah, "CAD-CAM integration using machining features," *International Journal of Computer Integrated Manufacturing*, pp. 296-318, 2002.
- [11] J. Shah and M. Rogers, "Assembly modelling as an extension of feature-based design," *M.T. Research in Engineering Design*, vol. 5, pp. 218-237, 1993.
- [12] S. Mullins and D. Anderson, "Automatic identification of geometric constraints in mechanical assemblies," *Computer-Aided Design*, vol. 30, no. 9, pp. 715-726, 1998.
- [13] W. Holland and W. Bronsvoort, "Assembly features in modeling and planning," *Robotics and Computer Integrated Manufacturing*, vol. 16, 277-294, 2000.

- [14] J. Shah, "Designing with parametric CAD: Classification and comparison of construction techniques," *Geometric Modelling: Theoretical and Computational Basis Towards Advanced CAD Applications*, vol. 75, pp. 53-68, 2001.
- [15] W. Van Holland, "Assembly features in modelling and planning," Ph.D. dissertation, Delft: Delft University of Technology, 1997.
- [16] K. Kim, "Assembly operation tools for. Assembly operation tools for e product design and realization," Ph.D. dissertation, Pittsburgh: University of Pittsburgh, 2003.
- [17] N. Shyamsundar and R. Gadh, "Internet-based collaborative product design with assembly features and virtual design spaces," *Computer-Aided Design*, vol. 33, pp. 637-651, 2001.
- [18] P. Singh and B. Bettig, "Port-compatibility and connectability based assembly design," *Journal of Computing and Information Science in Engineering*, vol. 4, pp. 197-205, 2004.
- [19] S. Myung and S. Han, "Knowledge-based parametric design of mechanical products based on configuration design method," *Expert Systems with Applications*, vol. 21, no. 2, pp. 99-107, 2001.
- [20] W. Bronsvoort, R. Bidarra, M. Dohmen, W. Van Holland, and K. de Kraker, "Multiple-view feature modelling and conversion," in *Geometric Modelling: Theory and Practice— the State of the Art*, Berlin, Springer, 1997, pp. 159-174.
- [21] E. Van den Berg, R. Bidarra, and W. Bronsvoort, "Web-based interaction on feature models," in *Proc. the Seventh IFIP WG 5.2*

International Workshop on Geometric Modelling: Fundamentals and Applications, 2000, pp. 113-123.

- [22] R. Bidarra and W. F. Bronsvoort, "Semantic feature modelling," *Computer-Aided Design*, vol. 32, no. 3, pp. 201-225, 2000.
- [23] J. Tan, L. Zhenyu, and Z. Shuyou, "Intelligent assembly modeling based on semantics knowledge in virtual environment," in *Proc.* the International Conference on Computer Supported Cooperative Work in Design, 2002, pp. 568-571.
- [24] L. Zhen-Yu, T. Jian-Rong, Z. Shu-You, and J. Zheng-Feng, "Design semantics of assembly modeling in virtual environment: expression, transfer and transformation," *Chinese Journal of Computers*, vol. 23, no. 11, pp. 1208-1214, 2000.
- [25] W. Hui, X. Dong, D. Guanghong, and Z. Linxuan, "Assembly planning based on semantic modeling approach," *Computers in Industry*, vol. 58, no. 3, pp. 227-239, 2007.
- [26] Y. S. Ma and T. Tong, "Associative feature modeling for concurrent engineering integration," *Computers in Industry*, vol. 51, no. 1, pp. 51-71, 2003.
- [27] Help 2016 S. A., 2016, [Online]. Available: http://help.solidworks.com/2016/English/api/sldworksapiprogguid e/Welcome.htm
- [28] A. Mathew, "A novel method of using API to generate liaison relationships from an assembly," *International Journal of Software Engineering and Applications*, vol. 1, no. 3, pp. 167-175, 2010.