Designing and Modeling of Quadcopter Control System Using L1 Adaptive Control

Kyaw Myat Thu and Gavrilov Alexander Igorevich

Department of Automatic Control Systems, Bauman Moscow State Technical University, Moscow, Russian Federation Email: mr.kyaw.myatthu@ieee.org, alexgavrilov@mail.ru

Abstract—Quadcopters have generated considerable interest in both the control community due to their complex dynamics and a lot of potentials in outdoor applications because of their advantages over regular aerial vehicles. This paper presents the design and new control method of a quadcopter using L1 adaptive control design process in which control parameters are systematically determined based on intuitively desired performance and robustness metrics set by the designer.

Index Terms—quadcopter; UAV; design; modeling; automatic control system; L1 adaptive control

I. INTRODUCTION

Unmanned Aerial Vehicles (UAVs) have become increasingly prominent in a variety of aerospace applications. The need to operate these vehicles in potentially constrained environments and make them robust to actuator failures and plant variations has brought about a renewed interest in adaptive control techniques [1]. Model Reference Adaptive Control (MRAC) has been widely used, but can be particularly susceptible to time delays. A filtered version of MRAC, termed L1 adaptive control, was developed to address these issues and offer a more realistic adaptive solution [2].

The main advantage of L1 adaptive control over other adaptive control algorithms such as MRAC is that L1 cleanly separates performance and robustness [3]. The inclusion of a low-pass filter not only guarantees a bandwidth-limited control signal, but also allows for an arbitrarily high adaptation rate limited only by available computational resources. This parameterizes the adaptive control problem into two very realistic constraints: actuator bandwidth and available computation. In this paper we consider the output feedback version of L1 described in [4]. This Single-Input Single-Output (SISO) formulation has several advantages. Foremost, the internal system states need not be modeled or measured. All that is required is a SISO input-output model that can encompass the entire closed-loop system and be acquired using simple system identification techniques. Thus the adaptive controller can be wrapped around an alreadystable closed-loop system [5], adding performance and robustness in the face of plant variations. It is also easy to

Manuscript received July 7, 2016; revised December 2, 2016.

predict the time-delay margin using standard linear systems analysis, and this margin has been confirmed experimentally. Finally, output-feedback L1 is relatively easy to implement in practice as will be seen in the experimental sections [6].

II. MODELING OF QUADCOPTER DYNAMIC

A. Reference System of Quadcopter

A quadcopter is an under actuated aircraft with fixed pitch angle four rotors as shown in Fig. 1. Modeling a vehicle such as a quadcopter is not an easy task because of its complex structure. The aim is to develop a model of the vehicle as realistically as possible.

A typical quadcopter have four rotors with fixed angles and they make quadcopter has four input forces, which are basically the thrust provided by each propellers as shown in Fig. 1. There are two possible configurations for most of quadcopter designs "+" and "x". An Xconfiguration quadcopter is considered to be more stable compared to + configuration, which is a more acrobatic configuration. Propellers 1 and 3 rotates counter clockwise (CW), 2 and 4 rotates counter-counter clockwise (CCW). So that, the quadcopter can maintain forward (backward) motion by increasing (decreasing) speed of front (rear) rotors speed while decreasing (increasing) rear (front) rotor speed simultaneously, which means changing the pitch angle. This process is required to compensate the action/reaction effect (Third Newton's Law). Propellers 1 and 3 have opposite pitch with respect to 2 and 4, so all thrusts have the same direction [7].



Figure 1. Two main types of quadcopter configuration.

There are two reference systems that have to be defined as a reference which are Inertial reference system

(Earth frame- XE, YE, ZE) and quadrotor reference system (Body frame- XB, YB, ZB). The reference system frames are shown in Fig. 2. The dynamics of quadcopter can be describe in many different ways such as quaternion, Euler angle and direction matrix. However, in designing attitude stabilization control reference in axis angle is needed, so the designed controller can achieve a stable flight. In attitude stabilization control, all angle references in each axis must be approximately zero especially when take-off, landing or hover. It ensures that, the quadcopter body always is in horizontal state, when external forces are applied on it [8]. The quadcopter orientation can be defined by three Euler angles which are roll angle (Φ), pitch angle (θ) and yaw angle (φ).



Figure 2. Forces, moments and reference systems of a quadcopter.

where,

 $\omega_1, \omega_2, \omega_3, \omega_4$: Rotation speeds (angular velocity) of the propellers

 T_1, T_2, T_3, T_4 : Forces generated by the propellers $F_i \propto \omega_i^2$: On the basis of propeller shape, air density, etc.

m: Mass of the quadcopter

mg: Weight of the quadcopter

 ϕ, θ, ψ : Roll, pitch and yaw angels

The position of the quadcopter is defined in the inertial frame x, y, z- axes with ξ . The attitude, i.e. the angular position, is defined in the inertial frame with three Euler angles η . Pitch angle θ determines the rotation of the quadcopter around the y-axis. Roll angle φ determines the rotation around the x-axis and yaw angle ψ around the z-axis. Vector q contains the linear and angular position vectors

$$\xi = \begin{bmatrix} x \\ y \\ z \end{bmatrix} \eta = \begin{bmatrix} \phi \\ \theta \\ \psi \end{bmatrix} q = \begin{bmatrix} \xi \\ \eta \end{bmatrix}$$
(1)

The origin of the body reference (body frame) is in the center of mass of the quadcopter. In the body frame, the linear velocities are determined by JB and the angular velocities by ω .

$$JB = \begin{bmatrix} Jx, B \\ Jy, B \\ Jz, B \end{bmatrix} \omega = \begin{bmatrix} p \\ q \\ r \end{bmatrix}$$
(2)

The rotation matrix from the body frame to the inertial frame is

$$R = \begin{pmatrix} c_{\psi}c_{\theta} & c_{\psi}s_{\theta}s_{\phi} - s_{\psi}c_{\phi} & c_{\psi}s_{\theta}c_{\phi} + s_{\psi}s_{\phi} \\ s_{\psi}c_{\theta} & s_{\psi}s_{\theta}s_{\phi} + c_{\psi}c_{\phi} & s_{\psi}s_{\theta}c_{\phi} - c_{\psi}s_{\phi} \\ -s_{\theta} & c_{\theta}s_{\phi} & c_{\theta}c_{\phi} \end{pmatrix}$$
(3)

in which $S_x = sin(x)$ and $C_x = cos(x)$. The rotation matrix *R* is orthogonal thus $R^{-1} = R^T$ which is the rotation matrix from the inertial frame to the body frame.

There are 3 types of angular speeds which can describe as the derivative of (φ, θ, ψ) with respect to time,

$$\phi$$
=Roll rate, θ =Pitch rate, ψ = Yaw rate

Considering the hovering condition of quadcopter gives 4 equations of forces, directions, moments and rotation speeds. Those are described by following,

Equilibrium of forces: $\sum_{i}^{4} = \mathbf{1} T_{i} = -mg$ Equilibrium of directions: $T_{1,2,3,4} \parallel g$ Equilibrium of moments: $\sum_{i}^{4} = \mathbf{1} M_{i} = \mathbf{0}$ Equilibrium of rotation speeds: $(\omega_{1} + \omega_{3}) - (\omega_{2} + \omega_{4}) = \mathbf{0}$,

And the consequence is:
$$\phi = 0$$
, $\theta = 0$, $\psi = 0$

By increasing/decreasing the rotation speed of all the propellers, the quadcopter can make movements flying up and down,

Flying up: $\sum_{i=1}^{4} T_{i} > -mg$,

Flying down: $\sum_{i=1}^{4} T_i < -mg$, Euler angles and rates remain 0.

Changing the equilibrium of propellers speed, directions and moments gives the following equations of yaw, roll and pitch of quadcopter.

Yaw:
$$\psi = k_Y((\omega_1 + \omega_3) - (\omega_2 + \omega_4)) \phi = \int \psi dt$$
 ⁽⁴⁾

Roll:
$$\dot{\phi} = k_R((\omega_1 + \omega_4) - (\omega_2 + \omega_3)) \phi = \int \dot{\phi} dt$$
 (5)

Pitch:
$$\dot{\theta} = k_P((\omega_1 + \omega_2) - (\omega_3 + \omega_4)) \theta = \int \dot{\theta} dt$$
 ⁽⁶⁾

Thus, decreasing the 2nd rotor velocity and increasing the 4th rotor velocity acquires the roll movement. Similarly, decreasing the 1st rotor velocity and increasing the 3th rotor velocity acquire the pitch movement. Increasing the angular velocities of two opposite rotors and decreasing the velocities of the other two acquire yaw movement.

B. Equation of Movements

$$\begin{pmatrix} \dot{\phi} \\ \dot{\theta} \\ \dot{\theta} \\ \dot{\psi} \\ F \end{pmatrix} = \begin{pmatrix} k & -k & -k & k \\ k & k & -k & -k \\ k & -k & k & -k \end{pmatrix} \begin{pmatrix} \omega_1 \\ \omega_2 \\ \omega_3 \\ \omega_4 \end{pmatrix}$$
(7)

$$\begin{pmatrix} \dot{\phi} \\ \dot{\theta} \\ \dot{\theta} \\ \dot{\psi} \\ F \\ F \\ F \\ \end{pmatrix} = \begin{pmatrix} k & -k & -k & k \\ k & k & -k & -k \\ k & -k & k & -k \\ k & k & k & k \end{pmatrix} \begin{pmatrix} \omega_1 \\ \omega_2 \\ \omega_3 \\ \omega_4 \\ \end{pmatrix} = \mathbf{K} \begin{pmatrix} \omega_1 \\ \omega_2 \\ \omega_3 \\ \omega_4 \\ \end{pmatrix}$$
(8)

According to equation (8), controlling the four input forces (roll, pitch, yaw, thrust) can be write down as below,



Figure 3. Controlling the Roll, Pitch, Yaw and total thrust forces.

III. L1 ADAPTIVE CONTROL ALGORITHM FOR QUADCOPTER FLIGHT CONTROL

Fig. 4 shows the closed-loop system with L1 adaptive controller. The controller includes a reference model and a lowpass filter C(s). Adding the low-pass filter C(s) does two important things. First, it limits the bandwidth of the control signal u being sent to the plant. Second, the portion of σ that gets sent into the reference model is the high-frequency portion.



Figure 4. L1 adaptive feedback control block diagram.

Closed-loop response

$$y(s) = H(s)C(s)r(s) - H(s)(1 - C(s))d(s)$$
Response to reference r(s)
Response to disturbance d(s)
(10)

where

$$H(s) = \frac{A(s)M(s)}{C(s)A(s) + (1 - C(s))M(s)}$$
(11)

Adaptive function and controller:

That is:

$$c(t) \coloneqq K_p e(t) + K_i \int_0^t e(\tau) d(\tau) + K_d \frac{de(t)}{dt}$$
(12)

In a discrete world (at k^{th} sampling instant):

$$C(k) \coloneqq K_{p} e(k) + K_{i} \sum_{j=0}^{k} e(j) \Delta T + K_{d} \frac{e(k) - e(k-1)}{\Delta T}$$
(13)

On the other hand, the L1 adaptive control system can be algorithmically described as following,



Figure 5. Full block diagram of the L1 adaptive control system of quadcopter.

IV. SIMULATION RESULTS

The mathematical model of the quadcopter is implemented for simulation in Matlab 2013 with Matlab programming language. Parameter values from [3] are used in the simulations and are presented in Table I.

TABLE I. PARAMETERS OF THE SYSTEM IN SI UNITS

Symbol	Quadcopter Parameters		
	Description	Value	Unit
g	Weight of the quadcopter	9.81	$[m/s^2]$
т	Mass of the quadcopter	0.75	[kg]
l	Distance from center to motor	0.26	[<i>m</i>]
Jx	Moment of inertia about <i>x</i> axis	0.019688	$[kgm^2]$
Jy	Moment of inertia about y axis	0.019688	$[kgm^2]$
Jz	Moment of inertia about z axis	0.03938	$[kgm^2]$
Kt	Propeller Force Constant	3.13 x 10 ⁻⁵	[Ns ²]
Kq	Propeller Torque Constant	7.5 x 10 ⁻⁷	[Ns ²]

Simulation results are shown in Fig. 6 and Fig. 7.

As can be seen from Fig. 6, the dynamics of the quadcopter with the proposed signal-parametric algorithm change rapidly as translational speed increases from a hover configuration. From Fig. 7 also shows that the signal-parametric algorithm has more accurate control ability, more spinning speed rotors that imposed the inability of the linear controller to accurately track forward velocities greater than 1.5 m/s. According to simulation results, the L1 adaptive controller shows improved performance for attitude and trajectory tracking of the quadcopter.



Figure 6. Measurement changing coordinates results when using the L1 adaptive control algorithm.



Figure 7. Measurement changing the angular velocities when using the L1 adaptive control algorithm.

V. CONCLUSIONS AND FUTURE WORKS

This paper attempts to provide a systematic design and modeling process for the use of L1 adaptive feedback control in realistic flight control applications. The proposed algorithm provides the control designer with an intuitive method linking relevant performance and robustness metrics to the selection of the L1 parameters. This modeling process represents a step in the direction of more easily applying L1 adaptive control to real-world flight systems and taking advantage of its potential benefits.

ACKNOWLEDGMENT

The authors would like to give special thanks to Naira Hovakimyan, Dapeng Li, and Eugene Lavretsky for their patient and expert advice regarding all matters adaptive. Thanks also to Buddy Michini and Jonathan P. How for their helpful papers and research jobs related to adaptive control systems. Especially thanks to supervisor of this work Assistant professor A.I. Gavrilov from the department of Automatic control systems.

REFERENCES

- A. I. Gavrilov, K. M. Thu, and E. A. Budnikova, "Synthesis of automatic control system quadrocopter," *International Conference* on Control in Marine and Aerospace System, St.Petersburg, Russia, UMAS-2014, 2014.
- [2] C. Cao and N. Hovakimyan, "L1 Adaptive controller for systems with unknown time-varying parameters and disturbances in the presence of non-zero trajectory initialization error," *International Journal of Control*, vol. 81, no. 7, 1147–1161, July 2008
- [3] E. Kharisov, N. Hovakimyan, and K. Astrom, "Comparison of several adaptive controllers according to their robustness metrics," in *Proc. AIAA Guidance, Navigation and Control Conference*, Toronto, Canada, AIAA-2010-8047, 2010.
- [4] C. Cao and N. Hovakimyan, "Design and analysis of a novel 11 adaptive control architecture with guaranteed transient performance," *IEEE Transactions on Automatic Control*, vol. 53, no. 2, pp. 586-591, 2008.
- [5] B. Michini and J. P. How, "L1 adaptive control for indoor autonomous vehicles: design process and flight testing," in *Proc. AIAA Guidance, Navigation and Control Conference*, Chicago, Illinois, AIAA-2009-5754, 2009.
- [6] M. Q. Huynh, W. H. Zhao, and L. H. Xie, "L1 adaptive control for quadcopter: Design and implementation," in *Proc. 13th International Conference on IEEE Control Automation Robotics* & Vision, Singapore, 2014.
- [7] K. M. Thu and A. I. Gavrilov, "Analysis, design and implementation of quadcopter control system," in Proc. 5th International Workshop on Computer Science and Engineering: Information Processing and Control Engineering, WCSE 2015-IPCE, Moscow, Russia, 2015.
- [8] H. A. F. Almurib, P. T. Nathan, and T. N. Kumar, "Control and path planning of quadrotor aerial vehicles for search and rescue," in *Proc. SICE Annual Conference*, 2011, pp. 700-705.

Kyaw Myat Thu was born in 1984. In 2009 he graduated with specialty "Rocket Engines" from the Bauman Moscow State Technical University. His research features unmanned aerial vehicles, adaptive and automatic control systems and data analysis.

After he received his master degree, he started to work in Defense Services Science and Technology Research Center, Myanmar for 15 months. Now 3rd year PhD Student of the Department "Automatic Control Systems" of the Bauman Moscow State Technical University.

He was the Session Chair of the IEEE International Conference on Modelling & Simulation (UKSim2016) held in Emmanuel College, Cambridge, United Kingdom. He is currently a member of IEEE society.

Gavrilov Aleksandr Igorevich, candidate of technical Sciences, associate Professor of the Department of automatic control Systems of Bauman Moscow State Technical University (BMSTU). His main research interests include: artificial intelligence, automatic control Systems, automata theory, theoretical computer science, pattern recognition.